

Engine List - Cummins

| Genset Model | Prime power/ Standby power | | Engine model | Fuel consumption L/h | Cylinder | Displacement P (L) | Genset Dimension (mm) | Weight (kg) |
|--------------|-------------------------------|---------|--------------|-------------------------|----------|-----------------------|-----------------------------|----------------|
| | KVA | KW | | | | | | |
| GHPC28-I | 25/28 | 20/22 | 4B3.9-G1 | 7.1 | 4L | 3.9 | 1680x730x1285 | 650 |
| GHPC28-II | 25/28 | 20/22 | 4B3.9-G2 | 6.7 | 4L | 3.9 | 1608x730x1285 | 650 |
| GHPC41-I | 38/41 | 30/33 | 4BT3.9-G1 | 10.0 | 4L | 3.9 | 1660x730x1285 | 700 |
| GHPC41-II | 38/41 | 30/33 | 4BT3.9-G2 | 9.3 | 4L | 3.9 | 1660x730x1285 | 700 |
| GHPC55 | 50/66 | 40/44 | 4BTA3.9-G2 | 12.9 | 4L | 3.9 | 1700x730x1285 | 770 |
| GHPC63 | 56/63 | 45/50 | 4BTA3.9-G2 | 14.9 | 4L | 3.9 | 1730x730x1285 | 800 |
| GHPC69 | 63/69 | 50/55 | 4BTA3.9-G2 | 14.9 | 4L | 3.9 | 1730x730x1285 | 800 |
| GHPC88 | 80/88 | 64/70 | 4BTA3.9-G11 | 17.6 | 4L | 3.9 | 1730x730x1285 | 800 |
| GHPC103-I | 94/103 | 75/83 | 6BT5.9-G1 | 21.7 | 6L | 5.9 | 2085x785x1550 | 1100 |
| GHPC103-II | 94/103 | 75/83 | 6BT5.9-G2 | 22.0 | 6L | 5.9 | 2085x785x1550 | 1100 |
| GHPC110-I | 100/110 | 80/88 | 6BT5.9-G1 | 21.7 | 6L | 5.9 | 2085x785x1550 | 1100 |
| GHPC110-II | 100/110 | 80/88 | 6BT5.9-G2 | 22.0 | 6L | 5.9 | 2085x785x1550 | 1100 |
| GHPC138-I | 125/138 | 100/110 | 6BTA5.9-G2 | 27.0 | 6L | 5.9 | 2145x785x1550 | 1250 |
| GHPC138-II | 125/138 | 100/110 | 6BTAA5.9-G2 | 30.0 | 6L | 5.9 | 2215x785x1550 | 1250 |
| GHPC150 | 135/150 | 108/120 | 6BTAA5.9-G2 | 30.0 | 6L | 5.9 | 2215x785x1550 | 1250 |
| GHPC165-I | 150/165 | 120/132 | 6BTAA5.9-G12 | 34.0 | 6L | 5.9 | 2255x840x1560 | 1600 |
| GHPC165-II | 150/165 | 120/132 | 6CTA8.3-G2 | 42.0 | 6L | 8.3 | 2255x840x1560 | 1600 |
| GHPC165-III | 150/165 | 120/132 | 6CTA8.3-G1 | 42.0 | 6L | 8.3 | 2255x840x1560 | 1600 |
| GHPC206-I | 188/206 | 150/165 | 6CTA8.3-G1 | 42.0 | 6L | 8.3 | 2255x840x1560 | 1600 |
| GHPC206-II | 188/206 | 150/165 | 6CTA8.3-G2 | 42.0 | 6L | 8.3 | 2370x840x1560 | 1800 |
| GHPC220 | 200/220 | 160/176 | 6CTAA8.3-G2 | 45.0 | 6L | 8.3 | 2460x945x1560 | 1800 |
| GHPC275-I | 250/275 | 200/220 | 6LTAA8.9-G2 | 53.0 | 6L | 8.9 | 2570x950x1560 | 2000 |
| GHPC275-II | 250/275 | 200/220 | 6LTAA8.9-G3 | 54.0 | 6L | 8.9 | 2570x950x1560 | 2000 |
| GHPC344 | 313/344 | 250/275 | QSM11-G2 | 69.0 | 6L | 10.8 | 2915x1000x1700 | 2500 |
| GHPC413-I | 375/413 | 300/330 | 6ZTAA13-G3 | 76.5 | 6L | 13.0 | 2915x1000x1700 | 2700 |
| GHPC480 | 440/480 | 350/385 | 6ZTAA13-G2 | 89.1 | 6L | 13.0 | 2956x1360x1855 | 2900 |
| GHPC500-I | 450/500 | 360/400 | 6ZTAA13-G4 | 91.4 | 6L | 13.0 | 2956x1360x1855 | 3000 |
| GHPC500-II | 450/500 | 360/400 | QSZ13-G2 | 70.4 | 6L | 13.0 | 2956x1360x1855 | 3000 |
| GHPC550-I | 500/550 | 400/440 | QSZ13-G3 | 101.0 | 6L | 13.0 | 3066x1360x1855 | 3200 |
| GHPC275-III | 250/275 | 200/220 | NT855-GA | 53.0 | 6L | 10.8 | 2930x1010x1710 | 2200 |
| GHPC275-IV | 250/275 | 200/220 | MTA11-G2A | 55.0 | 6L | 10.8 | 2840x1010x1710 | 2200 |
| GHPC275-V | 250/275 | 200/220 | MTA11-G2 | 52.0 | 6L | 14.0 | 2840x1010x1710 | 2200 |
| GHPC275-VI | 250/275 | 200/220 | NTA855-G1 | 59.0 | 6L | 14.0 | 2930x1010x1710 | 2800 |
| GHPC313 | 275/313 | 220/250 | NTA855-G1A | 61.0 | 6L | 14.0 | 2930x1010x1710 | 2850 |
| GHPC350-I | 313/350 | 250/280 | MTAA11-G3 | 61.3 | 6L | 14.0 | 2940x1010x1710 | 2500 |
| GHPC350-II | 313/350 | 250/280 | NTA855-G1B | 68.0 | 6L | 14.0 | 3066x1010x1710 | 3000 |
| GHPC350-III | 313/350 | 250/280 | NTA855-G2 | 68.0 | 6L | 14.0 | 3066x1010x1710 | 3000 |
| GHPC375 | 344/375 | 275/300 | NTA855-G2A | 72.0 | 6L | 14.0 | 2886x1010x1710 | 3000 |
| GHPC388 | 350/388 | 280/310 | NTA855-G4 | 75.0 | 6L | 14.0 | 2886x1010x1710 | 3100 |

| Genset Model | Prime power/ Standby power | | Engine model | Fuel consumption L/h | Cylinder | Displacement P (L) | Genset Dimension (mm) | Weight (kg) |
|--------------|-------------------------------|-----------|--------------|----------------------|----------|--------------------|-----------------------|-------------|
| | KVA | KW | | | | | | |
| GHPC413-II | 375/413 | 300/330 | NTAA855-G7 | 86.0 | 6L | 14.0 | 3006x1120x1710 | 3150 |
| GHPC450 | ----/450 | ----/360 | NTAA855-G7A | 98.0 | 6L | 14.0 | 3066x1120x1710 | 3400 |
| GHPC413-III | 375/413 | 300/330 | KTA19-G2 | 83.0 | 6L | 18.9 | 3066x1245x1990 | 3500 |
| GHPC500-11 | 450/500 | 360/400 | KTA19-G3 | 97.0 | 6L | 18.9 | 3126x1245x1990 | 3600 |
| GHPC550-II | 500/550 | 400/450 | KTA19-G3A | 106.9 | 6L | 19.0 | 3226x1245x1990 | 4000 |
| GHPC550-III | 500/550 | 400/450 | KTA19-G4 | 107.0 | 6L | 18.9 | 3226x1245x1990 | 4000 |
| GHPC630 | 525/630 | 420/505 | KTAA19-G5 | 113.0 | 6L | 18.9 | 3246x1245x1990 | 4100 |
| GHPC650-I | 575/650 | 460/520 | KTAA19-G6 | 118.5 | 6L | 18.9 | 3366x1550x2200 | 4350 |
| GHPC650-II | ----/650 | ----/520 | KTA19-G8 | 141.4 | 6L | 18.9 | 3366x1550x2200 | 4400 |
| GHPC688 | ----/688 | ----/550 | KTAA19-G6A | 155.0 | 6L | 18.9 | 3462x1550x2200 | 4500 |
| GHPC700 | 625/700 | 500/560 | KT38-G | 140.0 | 12V | 37.8 | 3952x1800x2520 | 6500 |
| GHPC713 | 650/713 | 520/570 | QSKTAA 19-G4 | 143.0 | 6L | 19.0 | 3462x1550x2200 | 4700 |
| GHPC788 | 713/788 | 570/630 | KTA38-G1 | 160.4 | 12V | 37.8 | 4052x1800x2520 | 6500 |
| GHPC800 | ----/800 | ----/640 | KT38-GA | 168.2 | 12V | 37.8 | 4052x1800x2520 | 6500 |
| GHPC825 | 750/825 | 600/660 | KTA38-G2 | 167.0 | 12V | 37.8 | 4052x1800x2520 | 6500 |
| GHPC888 | 800/888 | 640/710 | KTA38-G2B | 167.3 | 12V | 37.8 | 4052x1800x2520 | 6500 |
| GHPC1000 | 910/1000 | 728/800 | KTA38-G2A | 191.0 | 12V | 37.8 | 4152x1800x2520 | 7000 |
| GHPC1100 | 1000/1100 | 800/880 | KTA38-G5 | 209.0 | 12V | 37.8 | 4152x1800x2520 | 7200 |
| GHPC1250 | ----/1250 | ----/1000 | KTA38-G9 | 247.5 | 12V | 37.8 | 4128x2080x2520 | 8000 |
| GHPC1375-1 | 1250/1375 | 1000/1100 | QSK38-G5 | 274.0 | 12V | 37.7 | 4188x2180x2750 | 8200 |
| GHPC1375-11 | 1250/1375 | 1000/1100 | KTA50-G3 | 254.0 | 16V | 50.3 | 4618x1850x2750 | 8800 |
| GHPC1650-I | 1375/1650 | 1100/1320 | KTA50-G8 | 289.0 | 16V | 50.3 | 5138x2120x2900 | 9600 |
| GHPC1650-II | 1500/1650 | 1200/1320 | KTA50-GS8 | 308.8 | 16V | 50.3 | 5138x2120x2900 | 9800 |
| GHPC2000 | 1875/2000 | 1500/1600 | QSK60G3 | 371.0 | 16V | 60.2 | 6175x2287x2537 | 15152 |
| GHPC2250 | 2045/2250 | 1636/1800 | QSK60G4 | 394.0 | 16V | 60.2 | 6175x2287x2537 | 15366 |
| GHPC2500 | ----/2500 | ----/2000 | QSK60G13 | 399.0 | 16V | 60.2 | 6175x2287x2537 | 15500 |

STANDARD CONFIGURATION:

Generator Set Included:

Diesel engine, Alternator, Cooling Radiator, Automatic Control Panel, Output Circuit Breaker Box, Built-in Anti-vibration Pad, Hi-strength Base Frame

Accessories Included:

Exhaust Silencer, Bellow; Elbow and Flange, Starting Battery, Battery Switch with Cables

Documents Included:

Manual Book, Product Qualified Card

